



PAVEMENT CUT AND PATCH DETAIL

NOTES:

1. WHERE SOIL CONDITIONS CAN NOT BE MAINTAINED AS SHOWN ABOVE, PROVIDE APPROVED METHOD OF CONSTRUCTION.
2. SHEETING WILL BE REQUIRED AS DETERMINED IN THE FIELD.
3. NEW SURFACING MATERIALS SHALL BE CONSISTENT WITH EXISTING AND SHALL HAVE LAPPED & FEATHERED JOINTS (1 1/2" MIN. THK.)
4. COMPACTION PERCENTAGES SHOWN REFER TO A.A.S.H.T.O. T-180. PROVIDE COMPACTION TEST REPORTS TO CITY INSPECTOR.
5. MECHANICAL COMPACTION NOT ALLOWED BELOW THIS LEVEL.
6. INSTALL METALLIC TAPE OVER FULL LENGTH OF PIPE.
7. EIGHT INCHES (8") OF HIGH EARLY-STRENGTH CONCRETE MAY BE SUBSTITUTED FOR LIMEROCK UPON APPROVAL BY CITY ENGINEER.



STANDARD CONSTRUCTION DETAIL  
PAVEMENT CUT AND PATCH  
NTS

INDEX

R-8

MAY 2020